



Kubebooth Technical Data Sheet - KSelf*i* Floorless



Power Cord 10ft cord 120V/15Amp

Wall Construction Galvanized steel frames Sound insulation in all cavities

Door Lock Patch fit low noise- silent latch

Finishes TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

Easy to Install

Size Overall - W: 44" - D: 37" - H: 88" Inside - W: 36" - D: 36" - H: 84"

Weight 750 lbs/340 kg

Glass

10mm clear tempered Door - H: 88" x W: 32" Rear Panel - H: 88" x W: 44" Front Side Panel - H: 88" x W: 12"

Reversible Door

Fully interchangeable left or right opening

Plug & Play

Acoustics

Air Exchange

Data Center

UL approved

2 Simplex outlets

Class A noise reduction

1 USB A port, 1 USB C port

100 complete air changes per hour

Motion detector (controls light & fan)

Worktop

White or Black laminate wood worktop W: 20" x L: 12" Installed at an optimum height of 40"

Felt Interior sound absorption panels 60% recyclable

Options

Seismic bracing One touch LCD control panel LCD TV mount bracing White glass board - W: 34" x L: 30" Personalized company branding Ethernet ports Bluetooth speaker Frosted film glass External fire extinguisher unit Occupancy lights


Note: For your safety and optimal performance, this phone booth must be securely drilled to the floor during installation.



Light 12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation



*Air Flow Diagram