












Kubebooth Technical Data Sheet - KSelfi Floorless



Easy to Install

Size

Overall - W: 44" - D: 37" - H: 88" Inside - W: 36" - D: 36" - H: 84"

Weight

750 lbs/340 kg

Glass

10mm clear tempered Door - H: 88" x W: 32" Rear Panel - H: 88" x W: 44" Front Side Panel - H: 88" x W: 12"

Plug & Play

Acoustics

Class A noise reduction

Air Exchange

100 complete air changes per hour

Data Center

UL approved 1 USB A port, 1 USB C port 2 Simplex outlets Motion detector (controls light & fan)

Light

12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation

Power Cord 10ft cord 120V/15Amp

Wall Construction

Galvanized steel frames Sound insulation in all cavities

Door Lock

Patch fit low noise-silent latch

Finishes

TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

Reversible Door

Fully interchangeable left or right opening

Worktop

White or Black laminate wood worktop W: 20" x L: 12"
Installed at an optimum height of 40"

Fel

Note: For your safety and optimal performance, this phone booth


must be securely drilled to the floor during installation.

Interior sound absorption panels 60% recyclable

Options

Seismic bracing
One touch LCD control panel LCD TV mount
bracing White glass board - W: 34" x L: 30"
Personalized company branding
Ethernet ports
Bluetooth speaker
Frosted film glass
External fire extinguisher unit

Occupancy lights



*Air Flow Diagram







