















Easy to Install

Size Overall - W: 56" - D: 48" - H: 88" Inside - W: 48" - D: 47" - H: 84"

Weight

950 lbs/431 kg

10mm clear tempered Door - H: 88" x W: 32"

Rear Panel - H: 88" x W: 44" Front Side Panels - H: 88" x W: 12" *Panel includes 2 piece glass

Plug & Play

Acoustics Class A noise reduction

Air Exchange

100 complete air changes per hour

Data Center

UL approved 1 USB A port, 1 USB C port, 2 Simplex outlets Motion detector (controls light & fan)

Light

12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation

Power Cord

10ft cord 120V/15Amp

Wall Construction

Galvanized steel frames Sound insulation in all cavities

TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

Door Lock

Patch fit low noise-silent latch

Reversible Door

Fully interchangeable left or right opening


Interior sound absorption panels 60% recyclable

Options

Seismic bracing One touch LCD control panel LCD TV mount bracing White glass board - W: 34" x L: 30" Personalized company branding Ethernet ports Bluetooth speaker Frosted film glass External fire extinguisher unit

Occupancy lights

Note: For your safety and optimal performance, this pod must be securely drilled to the floor during installation.



*Air Flow Diagram







