











Kubebooth Technical Data Sheet - Kteam 4

80"

Weight

Glass

1800 lbs/816 kg

10mm clear tempered

Door - H: 88" x W: 36"

Ceramic painted borders

Rear Panels - H: 88" x W: 44"

Front Side Panels - H: 88" x W: 28"



Extendable

Easy to Install

Size Overall - W: 88" - D: 73" - H: **Acoustics** 88" Inside - W: 80" - D: 72" - H: NIC rating

NIC rating of 36 dB certified Noise cancellation technology

Moveable

Air Exchange

100 complete air changes per hour

Data Center

UL approved 1 USB A port, 1 USB C port 2 Simplex outlets Motion detector (controls light & fan)

Mobility Kit

Includes casters with fasteners

Plug & Play

Light

12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation

Power Cord

10ft cord 120V/15Amp

Wall Construction

Galvanized steel frames Sound insulation in all cavities

Finishes

D-pull handle TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

Carpet

Shaw Commercial Philadelphia Ayers Hall II or equal Solution dyed polypropylene 28 oz, 10 gauge GreenGuard certified GLP8472 <450 NBS smoke

Floor Ceiling

Substructure-rated MDF on unitized steel base.

Reversible Door

Fully interchangeable left or right opening

Worktop


White or Black laminate wood worktop D Shape L: 45" x W: 24" Installed at an optimum height of 28"

Felt

Interior sound absorption panels 60% recyclable

Options

Seismic bracing
One touch LCD control panel
LCD TV mount bracing
White glass board - W: 34" x L: 30"
Personalized company branding
Ethernet ports
Bluetooth speaker
Frosted film glass
External fire extinguisher unit
Smart lock
Occupancy lights



*Air Flow Diagram







