



Kubebooth Technical Data Sheet - Kteam 6 Floorless

Extendable

Easy to Install

Size Overall - W: 88" - D: 109" - H: 88" Inside - W: 80" - D: 108" - H: 84"

Weight 2100 lbs/953 kg

Glass 10mm clear tempered Door - H: 88" x W: 36" Rear Panels - H: 88" x W: 44" Front Side Panels - H: 88" x W: 28"



Plug & Play

Acoustics Class A noise reduction

Air Exchange 100 complete air changes per hour

Data Center UL approved 1 USB A port, 1 USB C port

2 Simplex outlets Motion detector (controls light & fan) Light 12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Sprinkler Pre-engineered knockout hole for 3rd party sprinkler installation

Power Cord 10ft cord 120V/15Amp

Wall Construction Galvanized steel frames Sound insulation in all cavities

Finishes

TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

Door Lock Patch fit low noise- silent latch

Reversible Door Fully interchangeable left or right opening

Worktop


Black or White Laminate wood D shape worktop

Felt

Interior sound absorption panels 60% recyclable

Options

Seismic bracing One touch LCD control panel LCD TV mount bracing White glass board - W: 34" x L: 30" Personalized company branding Ethernet ports Bluetooth speaker Frosted film glass External fire extinguisher unit Door lock Occupancy lights



*Air Flow Diagram

Note: This collaborative pod requires drilling to the floor during installation to ensure stability and safety for multiple users.

