











# **Kubebooth Technical Data Sheet - Kteam 4 Floorless**

### **Extendable**

#### ..

Overall - W: 88" - D: 73" - H: 88" Inside - W: 80" - D: 72" - H: 84"

**Easy to Install** 

#### Weight

1600 lbs/726 kg

Glass 10mm clear tempered Door - H: 88" x W: 36" Rear Panels - H: 88" x W: 44" Front Side Panels - H: 88" x W: 28"

## Plug & Play

#### Acoustics

Class A noise reduction

#### Air Exchange

100 complete air changes per hour

#### **Data Center**

UL approved 1 USB A port, 1 USB C port 2 Simplex outlets Motion detector (controls light & fan)

#### Light

12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

#### Sprinkler

Pre-engineered knockout hole for 3rd party sprinkler installation

#### Power Cord

10ft cord 120V/15Amp

#### **Wall Construction**

Galvanized steel frames Sound insulation in all cavities

#### Finishes

TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted

#### Felt

Interior sound absorption panels 60% recyclable

#### **Door Lock**

Patch fit low noise-silent latch


## **Reversible Door** Fully interchangeable left or right opening

#### Worktop

White or Black Laminate wood D shape worktop L: 45" x W: 24" Installed at an optimum height of 28"

#### Options

Seismic bracing
One touch LCD control panel
LCD TV mount bracing
White glass board - W: 34" x L: 30"
Personalized company branding
Ethernet ports
Bluetooth speaker
Frosted film glass
External fire extinguisher unit
Door lock
Occupancy lights



\*Air Flow Diagram

Note: This collaborative pod requires drilling to the floor during installation to ensure stability and safety for multiple users.







