













Kubebooth Technical Data Sheet - Kwe Plus Floorless

Extendable

Easy to Install

Plug & Play

Size Overall - W: 88" - D: 48" - H: 88" Inside - W: 80" - D: 47" - H: 84"

Weight

1150 lbs/527 kg

Acoustics Class A noise reduction

Air Exchange

100 complete air changes per hour

Glass

10mm clear tempered Door - H: 88" x W: 32" Rear Panels - H: 88" x W: 44" Front Side Panels - H: 88" x W: 28"

Data Center

UL approved 1 USB A port, 1 USB C port 2 Simplex outlets Motion detector (controls light & fan)

12V LED light bar with magnet 570mm/pcs super light bar, 3500K, 12VDC

Sprinkler Pre-engineered knockout hole for 3rd party sprinkler installation **Power Cord**

10ft cord 120V/15Amp

Door Lock

Patch fit low noise-silent latch

Wall Construction

Galvanized steel frames Sound insulation in all cavities

Interior sound absorption panels 60% recyclable

Finishes

TFL surface CARB certified (zero/low formaldehyde emissions) Aluminum hardware painted


Reversible Door Fully interchangeable left or right opening

Worktop

White or Black laminate wood worktop D shape L: 31" x W:24" Installed at an optimum height of 28"

Options Seismic bracing One touch LCD control panel LCD TV mount bracing White glass board - W. 34" x L: 30" Personalized company branding Ethernet ports Bluetooth speaker Frosted film glass External fire extinguisher unit

Door lock Occupancy lights



*Air Flow Diagram

Note: This meeting pod must be drilled to the floor to maintain structural integrity and ensure user safety.







